




Product Data Sheet

UNICLASS L7315	
Cl/Sfb	(52.6)
October 2012	

VX-F065 Square rodding eye stainless steel



200x200mm Square Rodding Eyes (NPSM threaded or Direct Fit)

GEN code	Material	FIT	Finish		A	B	C	WTKG
VX-F065	Stainless Steel	NPSM	Standard 227110	Polished 234193	200	62	110	3.1
VX-F065	Stainless Steel	Direct Fit	Standard 233433	Polished 234194	200	62	110	3.1

General Description

200 x 200mm square rodding eye with a NPSM thread or plain spigot for direct fit. Supplied in a standard finish or in a polished finish to order.

Technical Specification

Material: Stainless steel
Loading : K3

Compatible Items

NPSM grating: All cast iron Floor gullies VX-F200, VX-F210, VX-F220, VX-F230
Raising pieces VX-F350

Direct fit grating: Pipework 110mm OD
Ensign, EEZI-FIT, Timesaver 416, other materials 110mm OD
Timesaver 437 using a TD02 stepped coupling

Options Security screws (bag of 4) VX-F420



Saint Gobain PAM
Lows Lane, Stanton-by-Dale
Ilkeston, Derbyshire, DE7 4QU
Sales : 0115 930 0630

Technical T:01952 262 529 F: 01952 262 592
E: technical.soildrain.uk.pam@saint-gobain.com